

Technical Data

Find the appropriate MSM PowerWinch for your sailing yacht



Material		Alu anodized, seawater resistant alloy				
Length of Boat	ft.	29-35	33-37	36-41	39-46	43-55
Rec. Size of Foresail	m ²	35	44	53	88	110
Sheet Ø	mm	8-12	8-14	8-14	10-18	10-22
Weight	kg	6,8	8,3	11,5	17,3	24
Drum Ø	mm	96	107	113	125	145
Base Ø	mm	150	168	180	215	240
Height of Winch	mm	199	215	225	260	315
Height of Sheet Entry	mm	72	82	99	110	125
Fixation Bolts		5 x M6	5 x M8	5 x M8	5 x M10	5 x M10
Pitch Circle Ø	mm	123	138	153	182	194
Voltage	V	12	12/24	12/24	12/24	12/24
Electric Power (max.)	W	500	700	800	1200	1500
Sheet Speed (unladen)	m/min	20	23	24	24	24

Accessories (optional at extra cost)

- Electric cable 50 mm², taylor made, ready for installation, highly flexible
- Wireless remote control, enabling operation of up to four winches
- Circuit breaker 150 A, also to be used as main circuit switch

Every winch is delivered incl. control unit, a suitable deck switch, fixation bolts, drilling template and detailed installation manual. Every winch is equipped with integrated automatic thermal overload protection of the motor. 2 years warranty.

We manufacture exclusively in Germany, employing most modern CNC lathe and milling mashines.